

Wireline baskets



Designed to meet harsh offshore environments, our offshore baskets are fully certified to DNV 2.7-1 / BSEN 12079 or ISO 10855 and available on a sale or rental basis.



Can't find what you are looking for?

Contact our global sales team at sales@oegoffshore.com or visit our website to find your regional representative at www.oeg.group

Key features

Offshore wireline baskets c/w certified lifting slings and shackles as standard

Internal tie down points

Forklift pockets

Stackable

Optional features

GPS tracking

Custom design and modifications available for purchase

Please check exact specifications with your local representative when ordering.

Metric | International standard

Type	External dimensions (LxWxH - mm)	Internal dimensions (LxWxH - mm)	Tare weight (kgs)	Payload (kgs)	Max gross weight (kgs)
12ft Wireline basket	3,658 x 1,212 x 723	3,458 x 1,012 x 380	1,030	4,000	5,030
20ft Wireline basket	6,096 x 1,212 x 730	5,908 x 1,000 x 380	1,550	5,000	6,550
24ft Wireline basket	7,300 x 1,212 x 730	7,112 x 1,000 x 380	1,810	5,000	6,810

Product datasheet

Wireline baskets

Imperial | International/US standard

Type	External dimensions (LxWxH - ft/in)	Internal dimensions (LxWxH - ft/in)	Tare weight (lbs)	Payload (lbs)	Max gross weight (lbs)
12ft Wireline basket	12' 0" x 3' 11.7" x 2' 4.5"	11' 4" x 3' 3.8" x 1' 3"	2,270	8,818	11,089
20ft Wireline basket	20' 0" x 3' 11.7" x 2' 4.7"	19' 4.5" x 3' 3.4" x 1' 3"	3,417	11,023	14,440
24ft Wireline basket	23' 11.4" x 3' 11.7" x 2' 4.7"	23' 4" x 3' 3.4" x 1' 3"	3,990	11,023	15,013