

Waste compactors

20M / 40M



Key features

- Compacts all types of waste
- Large load door for bulk handling (34 x 24")
- Waste bags ejected hydraulically for easy removal
- Hoses rated to 16,000 psi
- Enclosed drip pan
- In-bag compaction at a 5:1 safety ratio

OEG's **ENVIROPAK 20/40HM** compactors offer safe, simple, and reliable waste management solutions. Featuring a large loading door and integrated drip pan, they handle all types of waste efficiently while minimising mess. Safety is prioritised with a latch door designed for gradual release and a hydraulic system equipped with a relief valve. Each unit undergoes sandblasting to white metal, is zinc-coated, and seal-welded to ensure durability and resistance to corrosion.



Can't find what you are looking for?

Contact our global sales team at enviropak.sales@oegoffshore.com or visit our website to find your regional representative at www.oeg.group

Please check exact specifications with your local representative when ordering.

Imperial International/US standard		
Unit model	Model 20M	Model 40M
Capacity	20 ft ³	40 ft ³
Dimensions (HxWxD - in)	90 x 39 x 43"	118 x 56 x 52"
Deck space	12 ft ²	18 ft ²
Weight	2,320 lbs	2,450 lbs
Compaction force	28,000 lbs	40,000 lbs

Product datasheet

Waste compactors

20M / 40M

Imperial International/US standard		
Unit model	Model 20M	Model 40M
Electrical rating	5HP 15.5/7.8 AMPS	5HP 15.5/7.8 AMPS
Air requirement	100PSI / 75CFM	100PSI / 75CFM
Cycle time	35 seconds	45 seconds

Metric International standard		
Unit model	Model 20M	Model 40M
Capacity	0.57 m³	1.14 m³
Dimensions (HxWxD - mm)	2,286 x 991 x 1,093 mm	2,997 x 1,423 x 1,321 mm
Deck space	1.12 m²	1.68 m²
Weight	1,053 kg	1,112 kg
Compaction force	12,700 kg	18,143 kg
Electrical rating	5HP 15.5/7.8 AMPS	5HP 15.5/7.8 AMPS
Air requirement	100PSI / 75CFM	100PSI / 75CFM
Cycle time	35 seconds	45 seconds