

# Waste compactor

## 4000HM



OEG's **ENVIROPAK 4000HM** waste compactors compact hazardous waste inside UN/DOT approved 1 cubic yard corrugated disposable shipping containers with up to 60,000 pounds of compaction force. Compaction force is transferred directly to the compactor walls, eliminating distortion of the container.



### Can't find what you are looking for?

Contact our global sales team at [enviropak.sales@oegoffshore.com](mailto:enviropak.sales@oegoffshore.com) or visit our website to find your regional representative at [www.oeg.group](http://www.oeg.group)

Imperial   International/US standard	
Unit model	4000HM
Capacity	27 ft <sup>3</sup>
Dimensions (HxWxD - in)	117 x 51 x 53"
Deck space	18 ft <sup>2</sup>
Weight	3,500 lbs
Compaction force	60,000 lbs

## Key features

Automatic compactor operation, manually controlled hydraulic container eject function

1,000 pounds or 2,000 pounds capacity shipping containers, poly liners available

Optional hepa filtrations system available

Reduce disposal costs up to 90% by compacting hazardous wastes

UV light for sanitation

## Optional features

HEPA and HEGA filtration systems available

IP56 motor upgrade

Air manifold, non-explosion, or explosion proof control panel

Please check exact specifications with your local representative when ordering.

Product datasheet

# Waste compactor

## 4000HM

Imperial   International/US standard	
Unit model	4000HM
Electrical rating	5HP 230 460V 15.5 7.8 AMPS
Air requirement	100PSI / 175CFM
Cycle time	95 seconds
Oil capacity	10 gal.

Metric   International standard	
Unit model	4000HM
Capacity	0.76 m³
Dimensions (HxWxD - mm)	2,971 x 1,295 x 1,346 mm
Deck space	1.7 m²
Weight	1,589 kg
Compaction force	27,240 kg
Electrical rating	5HP 230 460V 15.5 7.8 AMPS
Air requirement	100PSI / 175CFM
Cycle time	95 seconds
Oil capacity	38 L