

Crushers

Drum crusher



Key features

Two handed operation for operator safety

Anvil support base to ensure drum integrity

Safety limit switch on door

Air or electric operation

UV light for sanitation

Hepa filtration available

Drip pan available

OEG's **ENVIROPAK** drum crushers compact waste into 55/85 gallon drums before crushing the waste further. The Drum Crushers can crush 55 gallon drums to 4" and reduce disposal costs of hazardous waste by compacting into UN/DOT approved drums. All units meet and exceed international MARPOL 73/78 Annex V and utilise UL listed components.



Can't find what you are looking for?

Contact our global sales team at enviropak.sales@oegoffshore.com or visit our website to find your regional representative at www.oeg.group

Please check exact specifications with your local representative when ordering.

Imperial | International/US standard

| Unit model | Model MPC40 | Model MPC60 | Model MPC85 |
|--------------------------------|----------------------------------|-----------------------------------|-------------------------------------|
| Capacity | 55 gal. | 55 gal. | 85 gal. |
| Dimensions (HxWxD - in) | 104 x 39 x 38" | 118 x 48 x 39" | 113 x 54 x 46" |
| Deck space | 10 ft ² | 13 ft ² | 17 ft ² |
| Weight | 1,615 lbs | 1,840 lbs | 3,100 lbs |
| Compaction force | 30,000 lbs | 60,000 lbs | 85,000 lbs |
| Electrical rating | 3HP 230/460V 7.8 / 2.9 AMP | 5HP 230/460V 15.5 / 7.8 AMP | 10HP 230/460V 26.8 / 13.4 AMP |

Product datasheet

Crushers

Drum crusher

| Imperial International/US standard | | | |
|--------------------------------------|------------------|------------------|------------------|
| Unit model | Model MPC40 | Model MPC60 | Model MPC85 |
| Air requirement | 100PSI / 175 CFM | 100PSI / 175 CFM | 100PSI / 175 CFM |
| Cycle time | 60 seconds | 96 seconds | 75 seconds |
| Oil capacity | 10 gal | 10 gal | 10 gal |
| In drum compaction | Yes | Yes | Yes |
| Drum compaction | No | Yes | Yes |

| Metric International standard | | | |
|---------------------------------|----------------------------------|-----------------------------------|-------------------------------------|
| Unit model | Model MPC40 | Model MPC60 | Model MPC85 |
| Capacity | 208 litres | 208 litres | 321 litres |
| Dimensions (HxWxD - mm) | 2,641 x 990 x 965 mm | 2,997 x 1,219 x 990 mm | 2,870 x 1,372 x 1,168 mm |
| Deck space | 1.0 m² | 1.2 m² | 1.6 m² |
| Weight | 733 kg | 835 kg | 1,406 kg |
| Compaction force | 13,607 kg | 27,215 kg | 38,555 kg |
| Electrical rating | 3HP 230/460V 7.8 / 2.9 AMP | 5HP 230/460V 15.5 / 7.8 AMP | 10HP 230/460V 26.8 / 13.4 AMP |
| Air requirement | 100PSI / 175 CFM | 100PSI / 175 CFM | 100PSI / 175 CFM |
| Cycle time | 60 seconds | 96 seconds | 75 seconds |
| Oil capacity | 37.8 litres | 37.8 litres | 37.8 litres |
| In drum compaction | Yes | Yes | Yes |
| Drum compaction | No | Yes | Yes |