

Waste compactors

Marine green series



Key features

Positive lock-in restraint system secures cart into compactor or to bulkhead

Enclosed structure for compaction operations

In-bag compaction at a 5:1 safety ratio

UV light for sanitation

OEG's patented **ENVIROPAK** Marine green series compactors segregate and compact solid waste materials into wheeled carts for recycling and convenience. The design means that no ramps are needed for placement and removal of carts and there is no compaction force on the wheels. All compactors meet and exceed international MARPOL 73/78 Annex V.



Can't find what you are looking for?

Contact our global sales team at enviropak.sales@oegoffshore.com or visit our website to find your regional representative at www.oeg.group

Please check exact specifications with your local representative when ordering.

Imperial | International/US standard

| Unit model | Model MG2 | Model MG5 | Model MG10 | Model MG15 |
|--------------------------------|-------------------|--------------------|--------------------|--------------------|
| Capacity | 7 ft ³ | 19 ft ³ | 45 ft ³ | 58 ft ³ |
| Dimensions (HxWxD - in) | 76 x 32 x 24" | 89 x 43 x 44" | 107 x 54 x 46" | 120 x 57 x 49" |
| Deck Space | 6 ft ² | 13 ft ² | 17 ft ² | 19 ft ² |
| Weight | 435 lbs | 800 lbs | 940 lbs | 1,100 lbs |
| Dimensions (cart) (HxWxD - in) | 28 x 25 x 22" | 43 x 40 x 43" | 56 x 48 x 44" | 60 x 46 x 47" |

Product datasheet

Waste compactors

Marine green series

| Imperial International/US standard | | | | |
|--------------------------------------|--|--|---------------------------------|---------------------------------|
| Unit model | Model MG2 | Model MG5 | Model MG10 | Model MG15 |
| Deck Space (cart) | 4 ft² | 11.6 ft² | 14 ft² | 15 ft² |
| Weight (cart) | 86 lbs | 250 lbs | 450 lbs | 500 lbs |
| Compaction Force | 10,000 lbs | 10,000 lbs | 30,000 lbs | 30,000 lbs |
| Bag Model | HV96033 | HV96024 | HV96030 | HV96027 |
| Bag SWL | 650 lbs | 600 lbs | 2,200 lbs | 2,200 lbs |
| Electrical Rating | 2HP 110/230/460V 14/5.8/2.9 AMPS | 2HP 110/230/460V 14/5.8/2.9 AMPS | 3HP 230/460V 7.8/3.9 AMPS | 3HP 230/460V 7.8/3.9 AMPS |
| Air Requirement | 100PSI / 125CFM | 100PSI / 125CFM | 100PSI / 125CFM | 100PSI / 125CFM |
| Cycle Time | 35 seconds | 35 seconds | 80 seconds | 80 seconds |
| Oil Capacity | 1.5 gal | 1.5 gal | 2.5 gal | 2.5 gal |

| Metric International standard | | | | |
|---------------------------------|--|--|---------------------------------|---------------------------------|
| Unit model | Model MG2 | Model MG5 | Model MG10 | Model MG15 |
| Capacity | 0.2 m³ | 0.52 m³ | 1.2 m³ | 1.6 m³ |
| Dimensions (HxWxD - mm) | 1,930 x 813 x 610 | 2,261 x 1,092 x 1,118 | 2,718 x 1,372 x 1,168 | 3,048 x 1,148 x 1,245 |
| Deck Space | 0.6 m² | 1.2 m² | 1.6 m² | 1.8 m² |
| Weight | 198 kg | 363 kg | 426 kg | 499 kg |
| Dimensions (cart) (HxWxD - mm) | 711 x 635 x 559 mm | 1,092 x 1,016 x 1,092 mm | 1,422 x 1,219 x 1,118 mm | 1,524 x 1,168 x 1,194 mm |
| Deck Space (cart) | 0.4 m² | 1.1 m² | 1.3 m² | 1.4 m² |
| Weight (cart) | 39 kg | 113kg | 204 kg | 227 kg |
| Compaction Force | 4,536 kg | 4,536 kg | 13,608 kg | 13,608 kg |
| Bag Model | HV96033 | HV96024 | HV96030 | HV96027 |
| Bag SWL | 295 kg | 272 kg | 997 kg | 997 kg |
| Electrical Rating | 2HP 110/230/460V 14/5.8/2.9 AMPS | 2HP 110/230/460V 14/5.8/2.9 AMPS | 3HP 230/460V 7.8/3.9 AMPS | 3HP 230/460V 7.8/3.9 AMPS |
| Air Requirement | 100PSI / 125CFM | 100PSI / 125CFM | 100PSI / 125CFM | 100PSI / 125CFM |
| Cycle Time | 35 seconds | 35 seconds | 80 seconds | 80 seconds |
| Oil Capacity | 5.6 L | 5.6 L | 9.5 L | 9.5 L |

E & OE - All dimensions and weights are accurate at the time of creation. Please check exact specifications of units when ordering.