

# Waste compactors

## Rollback series



### Key features

- Compacts all non-hazardous waste
- Air or electrically operated
- Hydraulic operated roll back top for easy loading and unloading
- 2" deep drip pan with drain
- In-bag compaction at a 5:1 safety ratio
- Food grinder attachment or filter available
- Crusher available

OEG's **ENVIROPAK** rollback series compactors provide safe, simple, and reliable solutions for compacting non-hazardous waste. Operator safety is prioritised with all moving parts being completely enclosed, while the hydraulically operated slow-release door ensures efficient waste removal and a drip pan ensures clean removal of any excess liquid. Drum crushing is seamlessly performed within the chamber without the need for an adaptor.



### Can't find what you are looking for?

Contact our global sales team at [enviropak.sales@oegoffshore.com](mailto:enviropak.sales@oegoffshore.com) or visit our website to find your regional representative at [www.oeg.group](http://www.oeg.group)

Please check exact specifications with your local representative when ordering.

Imperial   International/US standard			
Unit model	Model 3000RB	Model 4000RB	Model 5000RB
Capacity	30 ft <sup>3</sup>	40 ft <sup>3</sup>	50 ft <sup>3</sup>
Dimensions (HxWxD - in)	113 x 51 x 92"	113 x 60 x 91"	111 x 62 x 93"
Deck space	31 ft <sup>2</sup>	35 ft <sup>2</sup>	35 ft <sup>2</sup>
Weight	3,030 lbs	3,800 lbs	4,010 lbs
Compaction force	60,000 lbs	60,000 lbs	60,000 lbs

Product datasheet

# Waste compactors

## Rollback series

Imperial   International/US standard			
Unit model	Model 3000RB	Model 4000RB	Model 5000RB
Electrical rating	5HP 15.5/7.8 AMPS	5HP 15.5/7.8 AMPS	5HP 15.5/7.8 AMPS
Air requirement	100PSI / 175CFM	100PSI / 175CFM	100PSI / 175CFM
Cycle time	60 seconds	60 seconds	60 seconds

Metric   International standard			
Unit model	Model 3000RB	Model 4000RB	Model 5000RB
Capacity	0.85 m³	1.14 m³	1.42 m³
Dimensions (HxWxD - mm)	2,692 x 1,299 x 2,337 mm	2,871 x 1,524 x 2,312 mm	2,820 x 1,575 x 2,337 mm
Deck space	2.88 m²	3.25 m²	3.25 m²
Weight	1,377 kg	1,724 kg	1,822 kg
Compaction force	27,216 kg	27,216 kg	27,216 kg
Electrical rating	5HP 15.5/7.8 AMPS	5HP 15.5/7.8 AMPS	5HP 15.5/7.8 AMPS
Air requirement	100PSI / 175CFM	100PSI / 175CFM	100PSI / 175CFM
Cycle time	60 seconds	60 seconds	60 seconds