

Food grinder

Stainless steel



Key features

- Custom capacity options available
- Safety switch on lid to prevent injury
- UV light for sanitation

Application

- Restaurants
 - Food waste can be discharged via sewer system for reduced handling and disposal fees
- Galleys

OEG's **ENVIROPAK** stainless steel grinders are constructed from 316 stainless steel and can be installed indoors or outdoors. Food waste is processed into 1/4" shreds or less. All grinders meet and exceed international MARPOL 73/78 Annex V and use UL listed components.



Can't find what you are looking for?

Contact our global sales team at enviropak.sales@oegoffshore.com or visit our website to find your regional representative at www.oeg.group

Please check exact specifications with your local representative when ordering.

Imperial International/US standard	
Unit model	Model S05ES
Hopper capacity	5 gal.
Dimensions (HxWxD - mm)	41 x 30 x 25"
Deck space	5.2 ft²
Weight	375 lbs
Hp	5
Requirements	Electric / ExProof

Product datasheet

Food grinder

Stainless steel

Imperial | International/US standard

Unit model	Model S05ES
Load capacity	300 gallons/hr
Meals per Hour	2,800 mph
Discharge size	2" Camlock
Water inlet size	¾" lockable ball valve

Metric | International standard

Unit model	Model S05ES
Hopper capacity	19 litres
Dimensions (HxWxD - mm)	1,041 x 762 x 635 mm
Deck space	0.5 m²
Weight	170 kg
HP	5
Requirements	Electric / ExProof
Load capacity	300 gallons/hr
Meals per hour	2,800 mph
Discharge size	50mm Camlock
Water inlet size	19mm lockable ball valve