

Food grinder

Tuff gut



OEG's **ENVIROPAK** Tuff gut food grinders feature a revolutionary TEFC external motor design, engineered to withstand outdoor conditions while operating quietly indoors, with its external placement, the risk of motor burnouts from water damage is eliminated. The 5HP electric motor is securely housed in an explosion-proof enclosure, surpassing Class I Division II standards. All units meet and exceed international MARPOL 73/78 Annex V.



Can't find what you are looking for?

Contact our global sales team at enviropak.sales@oegoffshore.com or visit our website to find your regional representative at www.oeg.group

Imperial International/US standard	
Unit model	Tuff gut
Hopper capacity	5 gal.
Dimensions (HxWxD - mm)	36 x 27 x 27"
Weight	396 lbs
HP options	5, 7.5, 10, 15
Requirements	Electric / Ex-proof, Air*
Load capacity	300 gallons/hr
Water consumption	5 gal. per minute

*225 cfm required for air operation

HP Capabilities	
Unit model	Meals per hour
5 HP electric	2,800 mph
7.5 HP electric	3,500 mph
10 HP electric	4,400 mph
15 HP electric	5,200 mph
Air operated	4,100 mph

E & OE - All dimensions and weights are accurate at the time of creation. Please check exact specifications of units when ordering.

Key features

Standard offset inlet prevents accidental hand injury

Auto reversing blades

Electrical or air operation

UV light for sanitation

Optional magnetic catch guard to prevent accidental loss of silverware

Application

Restaurants

Galleys

Please check exact specifications with your local representative when ordering.

Product datasheet

Food grinder

Tuff gut

Metric International standard	
Unit model	Tuff gut
Hopper capacity	19 litres
Dimensions (HxWxD - mm)	914 x 686 x 686 mm
Weight	179 kg
HP options	5, 7.5, 10, 15
Requirements	Electric / Ex-proof, Air*
Load capacity	1,135 litres/hr
Water consumption	19 litres per minute

*225 cfm required for air operation