

Food grinder

Tuff gut II



OEG's **ENVIROPAK** Tuff gut II food grinders are designed for galley installation, but are suitable to withstand outdoor elements, built with an all stainless-steel structure and grinding components. The Tuff gut II is delivered ready to connect to the water supply, discharge and power supply for easy setup. All units meet and exceed international MARPOL 73/78 Annex V and IP55 protection class.



Can't find what you are looking for?

Contact our global sales team at enviropak.sales@oegoffshore.com or visit our website to find your regional representative at www.oeg.group

Imperial International/US standard		
Unit model	5 gallon sink	45 gallon sink
Hopper capacity	5 gal.	45 gal.
Dimensions (HxWxD - in)	41 x 31 x 26"	62 x 40 x 41"
Deck space	5.6 ft ²	11.4 ft ²
Weight	350 lbs.	700 lbs.
Hp	5, 7.5, 10, 15	10, 15, 20
Requirements	240 or 480 vac / 3 ph / 50 or 60 hz	240 or 480 vac / 3 ph / 50 or 60 hz
Load capacity	200 gallons / hr	400 gallons / hr

Key features

Safety switch on hopper lid prevents operation unless lid is closed

Hopper flusing nozzle

UV light for sanitation

Custom sink sizes and motors

Undersink or worktable models

Optional environmentally friendly Enz-Odours odour remover

Optional magnetic catch guard to prevent accidental loss of silverware

Application

Restaurants

Galleys

Outdoors

Please check exact specifications with your local representative when ordering.

Product datasheet

Food grinder

Tuff gut II

Metric International standard		
Unit model	5 gallon sink	45 gallon sink
Hopper capacity	19 litres	170 litres
Dimensions (HxWxD - mm)	1,044 x 805 x 652 mm	1,579 x 1,019 x 1,036 mm
Deck space	0.5 m²	1 m²
Weight	159 kg	318 kg
HP	5, 7.5, 10, 15	10, 15, 20
Requirements	240 or 480 vac / 3 ph / 50 or 60 hz	240 or 480 vac / 3 ph / 50 or 60 hz
Load capacity	750 litres / hr	1500 litres / hr